Muddy Waters A Discussion of Recent Turbidity measurements in the Delta

OCAP Workshop 2010


J.R. Burau 10/10/2010



Outline

- (1) What we did (installation of new sites)
- (2) What we learned
- a) Peaks in discharge and turbidity are not coincident during first flush
- c) Flooded Islands act as settling basins
- d) Turbidity field is complex
- (3) Data Products (web based)
- a) Time series package
- b) Scalar field interpolations

What we did: Installed about 12 turbidity stations



Location of PROPOSED (9/2009) sampling locations and the collected parameters in the Delta Area of California.


Field Team



Peaks in river discharge and turbidity are not coincident during first flush



Time-Series Data – Flow and Turbidity January-February, 2010



Management Implications? Control turbidities in central/south Delta through Operable gates in Georgiana and in the DCC DCC Close gates 60000 Freeport 50000 40000 www 30000 20000 10000 Freeport TURBIDITY, NTU Georgiana (upstream) 300 Mokelumne @ SJ 200

25

20

35

Open both sets of gates during day Close both sets of gates at night

30


50

JRB

100

DAYS FROM JANUARY 1, 2010

Effect on Western Delta net Flows from Closing Georgiana Slough?



If DCC were open even bigger impact (at least double)


Challenges to operating gates in DCC and Georgiana to alter Turbidity fields and Western delta hydrodynamics

- (1) Need to construct gate in Georgiana
- (2) DCC gates are currently closed to protect salmon
 - (3) Need to alter DCC closure requirement
 - @ Sac flows that exceed 25k cfs


Flooded Islands act like settling basins



Turbidities drop dramatically across Franks Tract




Turbidities drop dramatically across Franks Tract



Franks Tract – Tracer Dye Conservative – numerical model



Franks Tract – Jets Enhance mixing with ambient water - settling




Compare drop in turbidity

(a) Across channel without flooded Island (Old River)


against a

(b) Channel with flooded island (Middle River -Mildred Island)

Turbidity variability - Middle River



Turbidity variability - Old River




Steady decline in turbidity – no big drop

Web Based data analysis tools




Data are available in real-time cdec.water.ca.gov and baydelta live.com



Collaboration: John Donovan (USGS), Dave Osti (34north)


Interpolated Scalar Fields (Turbidity) Fields



Collaboration: John DeGeorge (RMA), Dave Osti (34north)

Next Steps in the Field


(1) Collect SSC boundary condition data



Proposed or existing locations for Suspended Solids Concentration (SSC) Calibration stations (red dot) and proposed additional flow+turbidity stations (yellow dot).


(2) Collect Acoustic Backscatter data

Flow Measurement Technologies



More reliable (less fouling), more representative

(2) Collect Acoustic Backscatter data



Location of USGS-operated flow station sites in the Delta Area of California.

